



CREATES BEST CONNECTIONS

ARDEX BU 2K

DIN 18195, . 4 – 6),
)

-

,
(
(



QM -

DIN EN ISO 9001

ARDEX GmbH
D- 58430 Witten · Postfach 61 20
Tel.: +49 (0) 23 02/664- 0
Fax: +49 (0) 23 02/664-240
kundendienst@ardex.de
www.ardex.de

ARDEX BU 2K

ARDEX BU 2K

ARDEX BU 2K

ARDEX BU-SB 240

DIN 18195-3 «
» DIN 1053 «

(100) .300
()

ARDEX BU - R.
DIN 18195, .5

ARDEX S 33.

DIN 18195, .5

ARDEX BU 1K-S,

2-5

a)

,20

20

b)

100 ².

>5
()

ARDEX BU-P

/			2
			1-2
(DIN 18195, . 4)	4,8	3,0	4,8
(DIN 18195, . 5)	4,8	3,0	4,8
(DIN 18195, . 6)	5,4	4,0	6,5
(3)	5,4	4,0	6,5
			1-2

:
 +5 - 30 °C.

DIN 18195, . 9.

DIN 18195, .

10.

ARDEX:

: 22 : 8
 : . 250 dPas*
 : . 1,2 /
(DIN ISO 3251 105 °C): > 60%
 : 5 *
 : 1-2 *
(E DIN 28052-6 +4 °C): ≥ 2
(DIN 52123): ≥ +70 °C
 ≥ 0 °C
(DIN 52123):
 -
(DIN 52123,
 -
1):
 : +5 - 30 °C
 : . 2-3 .*
GefStoffV: : «Xi »
GISCODE: BBP 10
 : 30
 2- +
 : . 12