



ARDEX SE

(-)

,

, - ,

-



ARDEX Baustoff GmbH
A-3382 Loosdorf, Hürmer Straße 40
Tel. 0 27 54/70 21-0
Fax 0 27 54/24 90
E-mail: office@ardex.at
Internet: www.ardex.at

ARDEX SE

10-12) (

ARDEX SG

SE ARDEX

) 25%.

ARDEX SE -

| | |
|----|---------|
| 10 | 6 |
| 10 | 8 - 10 |
| 15 | 8 - 12 |
| 20 | 10 - 14 |
| 25 | 12 - 18 |

25 % ARDEX SE

ARDEX SE 10

ARDEX SE ARDEX SE

5° C 40° C.

ARDEX SE -

ARDEX SE

ARDEX SE /

ARDEX SP 1,

ARDEX SP 2 ().

5 - 10

().

ARDEX SE

ARDEX SE.

ARDEX:

ARDEX SE

:
: 1-

ARDEX ST.

DIN 52451: .1 / ³
: 30

: 5° 40°C
()

*: .10 – 12 ()

*: 2 /
7 /

: -40° C 180°C

: .25 %

100 %: .0,40 / ²
(DIN EN 28339 A)

: .25

: 10 x 10 - .3 .

5 x 5 - .12 .

* +23°C . / 50 %.

: -310
20 ,

:
: .2

