



CREATES BEST CONNECTIONS

---

# ARDEX BM

---

( DIN 18195, . 4+5)

« »



Reg.No. 3/344

QM -

DIN EN ISO 9001

---

ARDEX GmbH  
D- 58430 Witten · Postfach 61 20  
Tel.: +49 (0) 23 02/664- 0  
Fax: +49 (0) 23 02/664-240  
kundendienst@ardex.de  
www.ardex.de

# ARDEX BM

ARDEX BM –

ARDEX BM-P.

ARDEX S 33.

ARDEX BU 2K,

ARDEX BU 1K – S

ARDEX BU 2 K.

ARDEX BM-P.

ARDEX BM

ARDEX BM

ARDEX BM -

ARDEX BM.

		<b>ARDEX:</b>	
		:	. 1,1 <sup>2</sup> / 2 <sup>2</sup>
		:	. 1,8 / 2 <sup>2</sup>
		:	1
	10	:	≥ 1,6
		:	- 5 - +30 °C
	ARDEX BM,	(DIN 52123):	≥ +70 °C
		(E DIN 28052-6):	≥ 5
2K-P	ARDEX BU 2K.	ARDEX BU	(DIN 52123, 12):
			≤ -30 °C
		(DIN 52123, 10.2):	≥ 4 / 24
	72	(DIN 4102):	B2
	-5 - +30 °C.	( / ): 235/220 / 50	
ARDEX BM		( / ): 200/225 %	
		<b>GefStoffV:</b>	
		:	5 <sup>2</sup> , 15 <sup>2</sup> 1
		:	;
			. 12