



AUS GUTEM GRUND

ARDEX S 21

ARDEX
(WSZ) 32,5 R-SF

- Z-3.12-1206

DIN 4102, . 1, , A2
Z - PA - III 4.594

ARDEX S 21
+ ARDEX E 90

=



QM –
DIN EN ISO 9001

ARDEX GmbH
D- 58430 Witten · Postfach 61 20
Tel.: +49 (0) 23 02/664- 0
Fax: +49 (0) 23 02/664-240
kundendienst @ ardex.de
www.ardex.de

ARDEX S 21

: 10
 ()
 0-4 1,0 .. 0,3 ..
 0-8 1,0 .. 0,5 ..
 :
 ARDEX E 90, 25 ARDEX S 21 .5
 1:1. 10 ()
 10
 :
 (ARDEX WSZ) 32,5 R-SF, ARDEX S 21
 Z-3.12-1206; ARDEX E 90 1:1.
 :
 « »
 :
 ARDEX E 90 -
 25 ARDEX S 21 = 1
 . 27 = 4
 . 4,5 =
 :
 ARDEX S 21
 :
 ARDEX P 51, « » - ()
 1:3. 90
 :
 ARDEX P 82. ARDEX S 21.
 :
 ARDEX
 ARDEX S 21 25
 4
 :
 ARDEX S 21,
 ()
 25 ARDEX S 21 4-5
 :
 20° C
 .90

ARDEX:

10
 3
 ARDEX S 21
 ARDEX E 90 1 : 1.
 25 ARDEX S 21 .2,5 ARDEX
 E 90 2,5

: .5 :25
 1 ... :3¹/₄ ...
 .4 :25
 1 ... :4¹/₄ ...
 : .1,5 /
 : .2 /
 :
 .1,7 / 2/ ;
 6 x 6 x 6 : .4 / 2

ARDEX.
 ARDEX -

(+20° C): .90
 : .10
 ()

ARDEX S 21
 5° C.

(+20° C): - 90 ;
 - 3
 : /

GISCODE ZP 1 =

: 1 .0,5 / 2
 28 .1-2 / 2
 : 1 .1-2 / 2
 3 .8 / 2
 28 .15 / 2
 : 1 .30 / 2
 3 .3 / 2
 28 .4 / 2
 .10 / 2

ARDEX S 21
 ARDEX E 90
 4,5 0,9
 : .12

ARDEX S 21
 25
 ARDEX E 90
 4,5 0,9
 : .12


ARDEX GmbH Friedrich - Ebert - Straße 45, D - 58453 Witten 04
EN 12004
C 1